

**NORDIC**



485



480



483



484



482



481

## NORDIC

### EN

Composition:	38% Cotton, 24% Acrylic, 18% Viscose, 12% Wool, 6% Polyester, 2% Polyamid
Maintenance:	Vacuum regularly or ☉ professional Dry-clean
Abrasion Resistance:	35.000 Martindale cycles
Flammability:	EN 1021 part 1&2

### DE

Zusammensetzung:	38% Baumwolle, 24% Akryl, 18% Viscose, 12% Wolle, 6% Polyester, 2% Polyamid
Reinigung:	Regelmässig staubsaugen. ☉ Professionelle Trockenreinigung
Scheuerfestigkeit:	35.000 Martindale
Feuerschutz:	EN 1021 part 1&2

### FR

Composition:	38% Coton, 24% Acryl, 18% Viscose, 12% Laine, 6% Polyester, 2% Polyamid
Nettoyage:	Aspirer régulièrement. ☉ Nettoyage á sec professionnel
Résistance á l'abrasion:	35.000 cycles Martindale
Normes au feu:	EN 1021 source d'ignition 1&2

### DK

Materiale:	38% Bomuld, 24% Akryl, 18% Viscose, 12% Uld, 6% Polyester, 2% Polyamid
Rengøring:	Støvsug regelmæssigt eller ☉ professionel rens
Slidstyrke:	35.000 Martindale
Flammesikring:	EN 1021 part 1&2