GUBI®

BESTLITE COLLECTION

BESTLITE BRASS BL9M // PENDANT, EU MODEL



Item no.: 001-0913X + style code

Don't polish the brass

DESCRIPTION

Bestlite has been in continuous production since 1930. Robert Dudley Best created Bestlite design. He was highly influenced by the Bauhaus. In the past 80 years, people appreciated the lamps and it decorates many homes, hotels and restaurants worldwide. Loved by architects, designers and design aficionados throughout its 80-year history, today, Bestlite enjoys global iconic status.

VERSION - BESTLITE PENDANT LAMP BL9M

Shade: Charcoalblack, Matt-White or Grey Ceiling cup: Brass with lacquered surface

Shade: Brass with lacquered surface Ceiling cup: Brass with lacquered surface

RAL codes are indicative.

- Fabric wire - Black:

- Charcoal black/Brass / White inside // RAL 9011 / RAL 9003 // Gloss level 20 / Gloss level 20 Grey w/Brass / White inside // RAL 2604005 / RAL 9003 // Gloss level 30 / Gloss level 20
Brass w/Brass / White inside // - / RAL 9003 // - / Gloss level 20

- Fabric wire - Off-White: - Matt-White w/Brass / White inside // RAL 9003 / RAL 9003 // Gloss level 20 / Gloss level 20

12 cm

21 cm

Please contact us for other colours or finishes.

VERSION

Order item - look for part number in the pricelist.

Series contains the following:

BL9S, BL9M, BL9L, BL9XL

3,5 cm

FACTS

MEASUREMENT - L X W X H MM Lamp rosette height: 35 mm Lamp rosette diameter: Ø120 mm Shade height: 180 mm Shade diameter: Ø210 mm Cord - total length w/sw: App. 2500 mm Cord - exposed out of lamp: App. 1980 mm

WEIGHT ITEM - LAMP INCL. WIRE 535 g

PACKAGING TYPE White cards rd box w/ 5ply corrugated

PACKAGING MEASUREMENT - L X W X H CM L:26 x W:40 x H:34 cm

WEIGHT PACKAGING - MATERIAL TYPE Bestlite brochure 120 x 170 mm: 66,5 g - Paper Egg crate: 456,5 g - Umbraco key: 5 g PE polybag:1 g - PE polybag: 60 g - Cardhoard insid le: 38 n - Cardboard outside: 532 g

WEIGHT PACKAGING - TOTAL 1629 g

NUMPER OF PARCELS 1 pcs.

LIGHT SOURCE: - Socket: E14 base Recommended light source: All fluorescens light bulbs
Recommended wattage: 9 W = (40 WATT incandescent bulbs)
Max wattage: 13 W

Recommended light source: Halogen light bulb - Recommended wattage: 28 W = (40 WATT inc nt bulbs) - Max wattage: 28 W

- All lamps can be fitted with a dimmer. Please contact your local electr

- Lightbulb not included

GUBI[®]

BESTLITE COLLECTION

BESTLITE BRASS BL9M // PENDANT, EU MODEL

Designed by Robert Dudley Best

CLEANING AND MAINTENANCE STANDARD Use a soft damp cloth when cleaning your Bestlite lamp. Do not use household cleaners. - Euro voltage: 230 V - Freqvency: 50 Hz ACCESSORIES - Supply voltage: AC power ~ - Normally Closed: IP20 CE ENVIRONMENT Class II / Double insulated CE-Mark TESTS F/ Luminaires accepted for mounting on a flammable base CERTIFICATION AND LABELS KOMPONENTS Item no.: 001-0913X CE-CERTIFIED 02 // Shade Ø21 cm. 05 // E14 lamp holder 10 // Insulating ring 11 // Internal shade ring 52 12 // External shade ring 13 // Lamp holder cover - 53 54 39 // Textile covered cord, round 53 // Mounting plate 53 // Ceiling cup 54 // Screw for ceiling cup


55 // Cord tube 56 // Screw for cord tube

56 // Screw for cord tub 59 // Pendant tube

MATERIAL Shade: Charcoalblack, White or Grey Ceiling cup: Brass with lacquered surface Textile covered cord

Shade: Brass with lacquered surface Ceiling cup: Brass with lacquered surface Textile covered cord

INSTALLATION INSTRUCTIONS



10 11

05

02