

VL RING CROWN TABLE LAMP

VL Ring Crown Table Lamp - 5744613334

The VL Ring Crown Table Lamp offers direct downward light through the opening at the bottom of the glossy, mouth-blown glass shade. The three-layered opal white glass provides soft, diffused and uniform illumination that surrounds the lamp, ensuring pleasant, glare-free lighting and an inviting ambience.



Vilhelm Lauritzen

Vilhelm Lauritzen (1894–1984) is one of the most significant architects in the history of Denmark; he was the trail-blazing figurehead of Danish functionalism. A number of his buildings – Nørrebro Theatre (1931–32), Daeils Varehus department store (1928–35), Radihuset (1936–41) and the first airport built in Kastrup (1937–39) – represented the concentrated essence of contemporary life.



Product info

Information

Please note that the brass surfaces are untreated. This means that the surface will change over time and develop a patina.

Mounting

3 m. White textile cord with plug. Switch on the base

Finish

Glossy, Mouth-blown, 3-layered, polished opal glass. Satin polished brass.

Materials

Mouth-blown 3-layered opal glass. Brass.

Sizes and weights

width x Height x Length (mm) | 273 x 1313 x 240 Max 2.2 kg

Class

Ingress protection IP20. Electric shock protection II.

Light source


1x40W E14

Information

Please note that the brass surfaces are untreated. This means that the surface will change over time and develop a patina.




Related products



VL Ring Crown 3-5-7 Pendant




VL Ring Crown 1 Pendant




VL Ring Crown 2 Wall Lamp




VL 45 Radiohus Pendant



VL Studio Table/Floor Lamp



VL Studio Wall Lamp



VL Ring Crown 1 Wall Lamp



VL Ring Crown Floor Lamp

Data specifications

Colour	Brass/opal glass	Length	240
Width	273	Height	1313
Built-in Height	-	IP class	-
Class	-	Net Weight	2.2
Standby (W)	-	Power Factor (P = 100 % / P = 50 %)	-
Inrush Current	-	Light source	1x40W E14
Kelvin	-	CRI	-
SDCM	-	Lumen	-
Watt	-	Efficacy	-
Light control	-	Min. Dim Level (%)	-
UGR Transversal / Axial	-	L80B50 (hours)	-
Driver life	-		