

m o o o i

Plié Plissé Light

LUKAS BAZLE



Plié Plissé Light by Lukas Bazle is inspired by the kinetic movements found in nature. This kinetic design has an adjustable cellular pleated shade that lets you choose the intensity and direction of the light. Unfolded, the light is soft and diffused. Perfect for (dinner) parties and lighting your whole room up. Fold the shade in and the lamp shines downwards and more intense, making it easier to work or read a book. As if dancing, Plié Plissé Light moves along with the rhythm of your day.

Detailing



Switch from ambient light to downward lighting with a simple movement.

Colours



White

Plié Plissé Light / Plié Plissé Light 60

Dimensions

60cm | 23.6"



38cm | 15"

Product

WIDTH 60cm | 23.6"

HEIGHT 38cm | 15"

DEPTH 60cm | 23.6"

DIAMETER 60cm | 23.6"

WEIGHT NETTO 0.7kg | 1.54lbs

Packaging

WIDTH 71cm | 28"

HEIGHT 47cm | 18.5"

CUBAGE 0.24m³ | 8.48ft³

LENGTH 71cm | 28"

WEIGHT 6kg | 13.23lbs

Technical CE

MATERIAL

Shade from non-woven PES (Plissé material), coated steel pendant

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Cylinder

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

10W

CABLE COLOUR

White

CANOPY

Pebble II White, ABS

CHROM Y

0.48

CRI

92

LIGHT OUTPUT

700 lm

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

60cm | 23.6"

FREQUENCY

50/60

LAMPHOLDER

E27

CABLE LENGTH

250cm | 98.4"

CHROM X

0.41

COLOUR TEMPERATURE

2500 K (max)

LIGHT DIRECTION

All directions

R9

0

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

Shade from non-woven PES (Plissé material), coated steel pendant

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

DIAMETER SHADE

60cm | 23.6"

INPUT VOLTAGE

100-120V

FREQUENCY

50/60

MAX POWER CONSUMPTION

10W

LAMPHOLDER

E26

CABLE COLOUR

White

CABLE LENGTH

250cm | 98.4"

CANOPY

Pebble II White, ABS

CHROM X

0.41

CHROM Y

0.48

COLOUR TEMPERATURE

2500 K (max)

CRI

92

LIGHT DIRECTION

All directions

LIGHT OUTPUT

700 lm

R9

0

DIMMING & LIGHTING CONTROL

Mains dimmable with compatible light source

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains dimmable with compatible light source

Compatible models: Plié Plissé Light 60 CE, Plié Plissé Light 60 UL
